

# RB<sup>®</sup> Real Bond

## WHY REAL BOND ?

With constant increase in sizes of tiles being produced in industry, there is an ever rising requirement of producing adhesive, which are suitable for laying such big sizes.

We have come up with a concrete solution for such sizes for the first time.

It can be used with any size tile under Indian weather conditions.

**For Enquiry & Feedback**  
**Customer Care**  
**+91 77373 73473**

## CHIMICO GLOBAL (INDIA)

Flat No.9, 3rd Floor, Aviratna, RDP1/5, Sector-2, Charkop West, Mumbai-400067

# RB<sup>®</sup> Real Bond

Easy to Use • Better Adhesion • Water Resistant  
**DEVELOPED FOR INDIAN WEATHER**

## ADHESIVE MORTAR

Exclusive for Ginormous Size Tiles

AN ISO 9001-2015 CERTIFIED COMPANY

# Real Bond

## How to Use



**1**  
Clean the surface thoroughly.  
Remove oil, dust and grease.

सतह को अच्छी तरह से साफ करें।  
तेल, धूल एवं मिट्टी को हटा दें।




**2**  
Pour water into bucket.


बाल्टी में पानी भरें।



**3**  
Add adequate quantity Real Bond  
adhesive mortar and mix.  
रीयल बॉण्ड एडेसिव को पानी की बाल्टी में उचित  
मात्रा में मिलायें।



**4**  
Apply the Real Bond adhesive mortar  
on the surface with smooth part of  
trowel.  
ट्रावल के सपाट हिस्से से सतह पर रीयल बॉण्ड  
एडेसिव फैलायें।




**5**  
For proper thickness spread the  
Real Bond adhesive Mortar using  
toothed part of trowel.

रीयल बॉण्ड एडेसिव की उपयुक्त  
मोटाई के लिए ट्रावल के दाँतों वाले  
हिस्से का इस्तेमाल करें।



**6**  
Apply Real Bond adhesive Mortar  
on the back of tile as required.  
आवश्यकतानुसार टाईल की पिछली  
सतह पर रीयल बॉण्ड एडेसिव लगायें।



**7**  
Clean excessive adhesive Mortar  
and lay the tile.  
एडेसिव की अतिरिक्त मात्रा को टाईल  
की सतह से निकाल कर टाईल लगा दें।



**8**  
Grout 24 hrs after fixing.  
फिक्सिंग के 24 घण्टे बाद ग्राउट भरें।

## Precautions

- The bedding layer should be in line and level with plain cement concrete / cement-sand mortar.
- Never to lay tile without leaving grooves. If no grooves left, the tiles fitted on wall is supported only on its back side, but in case of grooves provided, the grout supports the tiles on its four edges.
- To ensure proper application of the notched trowel, apply trowel preferable at right angle.
- To ensure immediate cleaning of edges of tile after pressing.
- Grouting to be done up to whole depth after proper hardening of adhesives.
- Finally, to smoothen grout filled in joints with a half cut PVC pipe by pressing and simultaneously moving it after wetting in water.

# Real Bond

## Description

Real Bond adhesive is a cement based adhesive mortar for high performance, high strength and superior quality laying of ginormous size tiles. It is suitable for internal and external flooring and wall cladding. It has a long open time with unsurpassed adhesion and workability.

## Features

Excellent bond strength, easy to spread, single component, easy mixing & application, consistent quality, no curing, extended open time, no wastage, ready to use.

## Coverage

25-50 sft per bag depending upon bed thickness.

## Color

White : This can be used with both light & dark shade of tiles.

## Packaging

It is available in 20 kg packing.

## Shelf Life

12 months from the date of manufacturing. Store in dry place free from moisture and water.

## Water Consumption

Approx 5.5 litres per bag (20kg).

## Pot Life

2 hrs at 27° ± 2°C